


Dunlap Stainless, Inc.


2905 Ramsey Road

Gainesville, GA 30507


(770) 531-1933 (Mon-Fri 8am-5pm)




Straight Tee



Reducing Tee



Eccentric Reducer



Concentric Reducer

NOM PIPE SIZE		OUTSIDE DIAM.		CENTER TO END		LENGTH
NPS X	NPS	OD ¹	OD ²	RUN C	OUTLET M	H
10	10	10.75	10.75	8.50	8.50	-
	8	10.75	8.62	8.50	8.00	7.00
	6	10.75	6.62	8.50	7.62	7.00
	5	10.75	5.56	8.50	7.50	7.00
	4	10.75	4.50	8.50	7.25	7.00
12	12	12.75	12.75	10.00	10.00	-
	10	12.75	10.75	10.00	9.50	8.00
	8	12.75	8.62	10.00	9.00	8.00
	6	12.75	6.62	10.00	8.62	8.00
	5	12.75	5.56	10.00	8.50	8.00
14	14	14.00	14.00	11.00	11.00	-
	12	14.00	12.75	11.00	10.62	13.00
	10	14.00	10.75	11.00	10.12	13.00
	8	14.00	8.62	11.00	9.75	13.00
	6	14.00	6.62	11.00	9.38	13.00
16	16	16.00	16.00	12.00	12.00	-
	14	16.00	14.00	12.00	12.00	14.00
	12	16.00	12.75	12.00	11.62	14.00
	10	16.00	10.75	12.00	11.12	14.00
	8	16.00	8.62	12.00	10.75	14.00
	6	16.00	6.62	12.00	10.38	-
	5	16.00	5.56	12.00	10.00	-
18	18	18.00	18.00	13.50	13.50	-
	16	18.00	16.00	13.50	13.00	15.00
	14	18.00	14.00	13.50	13.00	15.00
	12	18.00	12.75	13.50	12.62	15.00
	10	18.00	10.75	13.50	12.12	15.00
	8	18.00	8.62	13.50	11.75	-

NOM PIPE SIZE		OUTSIDE DIAM.		CENTER TO END		LENGTH
NPS X	NPS	OD ¹	OD ²	RUN C	OUTLET M	H
20	20	20.00	20.00	15.00	15.00	-
	18	20.00	18.00	15.00	14.50	20.00
	16	20.00	16.00	15.00	14.00	20.00
	14	20.00	14.00	15.00	14.00	20.00
	12	20.00	12.75	15.00	13.62	20.00
	10	20.00	10.75	15.00	13.12	20.00
	8	20.00	8.62	15.00	12.75	-
22	22	22.00	22.00	15.00	16.50	-
	20	22.00	20.00	16.50	16.00	20.00
	18	22.00	18.00	16.50	15.50	20.00
	16	22.00	16.00	16.50	15.00	20.00
	14	22.00	14.00	16.50	15.00	-
	12	22.00	12.75	16.50	14.62	-
24	24	24.00	24.00	17.00	17.00	-
	22	24.00	22.00	17.00	17.00	20.00
	20	24.00	20.00	17.00	17.00	20.00
	18	24.00	18.00	17.00	16.50	20.00
	16	24.00	16.00	17.00	16.00	20.00
	14	24.00	14.00	17.00	16.00	-
	12	24.00	12.75	17.00	15.62	-
	10	24.00	10.75	17.00	15.12	-

ALL DIMENSIONS ARE IN INCHES

ALL DIMENSIONS ARE IN ACCORDANCE WITH ASME/ANSI B16.9